

DESCRIPTION:

The JOC308XD4 series combine an AlGaAs infrared emitting diode as the emitter which is optically coupled to a monolithic silicon zero-cross photo triac in a plastic DIP4 package with different lead forming options. The products are widely used in solenoid/valve controls, lighting controls, motor controls, temperature controls, static AC power switches, solid state relays, interfacing microprocessors up to 265 V_{AC} peripherals.

MAIN FEATURES

High isolation 5000 VRMS

DC input with zero-cross photo triac output

Operating temperature range -55 - 125 °C


8 pins

HBM: 3000V

CQC approved

VDE approved

UL approved



ABSOLUTE MAXIMUM RATINGS (Temperature=25°C)

Parameter		Symbol	Value	Unit
Input	Forward Current	I_F	60	mA
	Reverse Voltage	V_R	6	V
	Junction Temperature	T_j	125	
	Input Power Dissipation	P_I	100	mW
	Power Dissipation Derating ($T_a > 125^\circ C$)	$\bullet P_D$	-1.33	mW/
Output	Off-state Output Terminal Voltage	V_{OFF}	800	V
	Peak Output Current	I_{TP}	2	A
	On-state RMS Current	$I_{T(RMS)}$	100	mA
	Peak Repetitive Surge Current ($P_W=10$ ms)	I_{TSM}	1	A
	Junction Temperature	T_j	125	
	Output Power Dissipation	P_O	250	mW

	Power Dissipation Derating (T_a 125)	$\bullet P_{D/}$	-3.33	mW/
Total Power Dissipation		P_{tot}	350	mW
Isolation Voltage		V_{iso}	5000'	Vrms
Operating Temperature		T_{opr}	-55~100	
Storage Temperature		T_{stg}	-55~125	
Soldering Temperature		T_{sol}	260 ⁸	

NOTE1AC for 1 minute, R.H.=40~60%


NOTE2For 10 seconds

ELECTRICAL CHARACTERISTICS (Sample Temperature=25°C)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit	
Input	Forward Voltage	V_F	$I_F=10mA$	-	1.27	2.2	V
	Reverse Current	I_R	$V_R=6V$	-	-	1	A
	Input Capacitance	C_{in}	$V=0, f=1kHz$	-	10	-	pF
Output	Peak Off-state Current, Either Direction	I_{OFF}	$V_{OFF}=800V, I_F=0$	-	-	100''	nA
	Peak On-state Voltage, Either Direction	V_{TM}	$I_{TM}=100mA$	-	1.7		

ORDERING AND MARKING INFORMATION

MARKING INFORMATION



Characteristics Curves

FIG.1: Forward Current vs. Ambient Temperature

FIG.2: On-state Terminal Current vs. Ambient Temperature

FIG.7: Normalized On-state Terminal Voltage vs. Ambient Temperature



FIG.8: On-state Terminal Voltage vs. On-state Terminal Current

TEST CIRCUITS


FIG.12: Test Circuits of Turn On Time

FIG.13: Waveforms of Turn On Time

Fig.14: Test Circuits of dV/dt


Fig.15: Waveforms of dV/dt

Option S Type:




Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	6.30		6.70	0.249		0.265
B	4.38		4.78	0.173		0.189
C	9.85		10.45	0.389		0.413
D	3.30		3.70	0.130		0.146
E	7.32		7.92	0.289		0.313
F		0.80			0.032	
G		0.25			0.010	
H		0.80			0.032	
I	1.20		1.40	0.047		0.055
J	4.00		4.60	0.158		0.182
K		2.54			0.100	

Option SL Type:




Option S LM Type:




Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	6.30		6.70	0.248		0.264
B	4.38		4.78	0.172		0.188
C	11.50		12.10	0.453		0.476
D	3.30		3.70	0.130		0.146
E	7.32		7.92	0.288		0.312
F						
G						
H	0.40			0.016		
I	1.20		1.40	0.047		0.055
J	3.45		4.05	0.136		0.159
K						
L						

TUBE SPECIFICATIONS (Dimensions in mm unless otherwise stated)

Standard DIP




Option M




Option SL(T3)

Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
D0						
P0						
P1		12.00			0.472	
P2						
E		1.75			0.069	
F		7.50				
T		0.40			0.016	
W		16.00			0.630	

REFLOW INFORMATION



WAVE SOLDERING



HAND SOLDERING BY SOLDERING IRON

Soldering Temperature	360 5
Soldering Time	3s max.

Document Revision History

Date	Revision	Changes
Apr.2, 2025	A.1.0	Last update
Nov.5, 2025	A.1.1	Add SLM package

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents.