

JST12C-800BW 12A TRIAC

Rev.A.1.1

DESCRIPTION:

The JST12C-800B

Peak pulse voltage (T _j =25℃ ; non-repetitive,off-state;FIG.7)	V _{pp}	4.5	kV
--	-----------------	-----	----

ORDERING INFORMATION

J ST 12 C -800 BW

JieJie Microelectronics Co., Ltd.

Triacs

BW800

800:V_{DRM} /V_{RRM} 1800V

FIG.1: Maximum power dissipation versus RMS
on-state current

FIG.2: RMS on-state current versus case
temperature

FIG.7 ÖTest circuit for inductive and resistive loads to IEC-61000-4-5 standards



ORDERING INFORMATION

Order code	Voltage $V_{\text{DRM}}/V_{\text{RRM}}$ (V)	IGT(mA)	Package	
------------	--	---------	---------	--

PACKAGE MECHANICAL DATA



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from